


Epoxy Table Installation Instructions

PLEASE READ THIS MANUAL THOROUGHLY BEFORE USING THIS
APPLIANCE



Round Table

Table Leg XTL-28 Installation Steps:

	Leveler	M6 screw	Suction Cup	Allen key
				
	x5	x8	x4	x1

Step 1: Attach first V- shaped frame to X-shaped frame

Take one V-shaped frame. Keep the tray style side facing upward. Align it with the four pre-drilled holes on left side of X-shaped frame, fasten with M6 screws.

Step 2: Attach second V- shaped frame to X-shaped frame

Take the other V-shaped frame, also keep its tray style side facing upward. Align with holes on right side of X-shaped frame, secure using M6 screws.

Important: The tray side with mounting holes on both X-shaped and V-shaped frames must face upward. A complete whole table base will be formed after assembly.

Step 3: Install levelers

Screw levelers into threaded holes at base. Rotate levelers to reduce wobble and stabilize the whole base on floor.

Step 4: Secure tabletop

First, screw the glass suction cups into the four holes on the mounting plate. Lay a soft cloth on the floor, then set your resin tabletop upside- down on top of the cloth to avoid scratches. Place the fully- assembled table base (with suction cups already attached) onto the tabletop. Let the suction cups lock in place, and your installation is finished.

